

ENVIRONMENTALLY RESPONSIBLE

GREEN IMPACT™

Speed Stripper

DESCRIPTION

GREEN IMPACT™ Stripper is a fast-acting speed stripper. This environmentally responsible formulation meets the Green Seal™ Standard for Industrial and Institutional Floor -Care Products (GS-40) and has been certified along with companion Green Seal™ Certified floor finishes.

GREEN IMPACT™ Stripper and companion Green Seal™ Certified Earth Sense® Floor Finishes are recommended for use in Federal, State and Local Government Offices, Military Bases, Municipal Facilities, Day Care Centers, Hospitals, Nursing Homes, Office Buildings, Parks and Recreation Centers, Schools, Universities, Hotels, Lodging and any facility sensitive to environmental and human health characteristics.

PRODUCT BENEFITS

- Non-toxic, non-flammable, non-caustic, environmentally responsible formula.
- No phosphates, no butyl (2-Butoxyethanol*), no NPE or APE surfactants, no free alkali, no added fragrances.
- Powerful, yet low odor formulation is excellent for use in health care facilities, nursing homes, any area where objectionable odors present a problem.
- Concentrated formula for economical in-use-dilution costs.

DIRECTIONS FOR USE

Mop/Wet Vacuum Stripping System: Dilute GREEN IMPACT™ using cold water according to the dilution chart below. Apply liberally with a mop to small area and allow to stand for 3 to 5 minutes. Add water to the floor as necessary to keep the floor from drying. Agitate with a mop and pick-up solution and old finish with a wet vacuum. Rinse as necessary. Allow floor to dry completely.

Floor Machine Stripping System: Dilute GREEN IMPACT™ using cold water according to the dilution chart below. GREEN IMPACT™ may be applied with a mop or Automatic Scrubber. Allow to stand for 3

to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Pick-up solution and old finish with a wet vacuum. Rinse as necessary. Allow floor to dry completely.

APPLICATION	OZ./GAL	DILUTION
Mop/Wet Vac		
Heavy Build-up	64	1:2
Normal Build-up	25	1:5
Floor Machine Stripping		
Normal Build-up	8	1:16
Heavy Build-up	25	1:5

SPECIFICATIONS

Color Clear Green
Odor Very Low, Neutral
pH (as is) 11.0 ± 0.3
pH (In dilution 1:2 to 1:16) 10.8 ± 0.4
Specific Gravity (g/cc) 1.00 ± 0.01
Lower Cloud Point < 33°F
Upper Cloud Point > 130°F

Viscosity (cps) < 5
Water Solubility Complete
Stripping Outstanding
Free Rinsing Yes
Low Odor Yes
Shelf Life 1 year minimum in original unopened container.

ENVIRONMENTAL RECOGNITIONS



The EARTH SENSE® Seal of Assurance is self-certified by NCL, and identifies our products that are formulated to promote human health and worker safety with a preferred environmental profile.



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

DISPOSE OF UNUSED PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS - PLEASE RECYCLE CONTAINER

PPE Information: Respiratory protection is generally not required. Use with adequate ventilation. The use of safety glasses and gloves is recommended. No other protective equipment is required.

ENVIRONMENTAL PROFILE

Chemical Ingredients:

Phosphates:None
Ammonia:None
2-Butoxyethanol*:None
APE / NPE:None
Added Fragrances:None
Free Alkali:None

Environmental Impact:

Harmful to Water Systems:No
Biodegradable:Readily
VOC Compliant (CARB, OTC) Yes
Recyclable Package Yes
Bio-Renewable Resources Yes
ReactiveNo
FlammableNo
CombustibleNo

Human Toxicity*:

Skin Corrosive:No
Eye Corrosive:No
Skin Sensitizer:No
Low Toxicity: Yes

* Human toxicity profile is based on ready-to-use product.



World Class Cleaning & Hygiene Solutions™

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com