



FAST BREAK™

Clean and Tack

DESCRIPTION

Fast drying formula cleans wood floors to restore natural beauty and luster. Tacking with **FastBreak™** cleans the surface, removing dust, dirt and grime and leaves no residue behind. Uses specially selected ingredients to remove soils from the wood surface.

PRODUCT FEATURES / BENEFITS

- Effectively removes dust and dirt.
- Fast drying, with no residue
- Recommended for use on all sealed wood floors.
- Recommended for use in wet screening process and as a final tack before applying new coatings.
- Low odor, no irritating fumes.

DIRECTIONS FOR USE

Directions:

FLOOR CLEANING:

Sweep, vacuum and/or dust mop floor surface prior to cleaning with **FastBreak™** Clean and Tack for optimum results. Dust mop floor surface using a untreated dust mop / microfiber dust mop.

WET SCREENING:

1. Mix **FastBreak™** at a ratio of 4 parts water to 1 part **FastBreak™** in a mop bucket or automatic scrubber. Use cool water only. Mount red or white cleaning pads.

2. FOR AN AUTOSCRUBBER: Autoscrub the floor surface in a single pass. Do not allow solution to stand on the floor surface. An individual with a pick-up mop or dry towels must follow behind the scrubber to pick up any water that is not picked up by the machine. Pay special attention to corners.

FOR A SWING MACHINE: Work in small areas. Apply solution to the floor using a mop or the automatic scrubber. Prep floor surface using a 175 rpm swing machine with a #120, #150, or Maroon floor pad. Use over lapping passes until floor surface is roughened evenly. Pick up dirty solution using a wet vacuum, mop and bucket, or automatic scrubber.

3. Rinse floor thoroughly and tack with **FastBreak™**. Allow floor surface to dry before walking on it.


TACKING WITH TOWELS:

1. In a mop bucket / wringer, mix **FastBreak™** Clean and Tack at a ratio of 4 parts water to 1 part **FastBreak™**. Use cool water only.

2. Soak the towels in the bucket of diluted solution. Make sure that they are completely wet. Wring out a towel thoroughly to remove excess cleaner solution until it is just damp.

3. Fold the dampened towel, place on the floor and wrap around a broom. Wipe the floor in long strokes without lifting the towel from the surface. Go with the grain of the wood. Reposition and refold towel frequently to expose a fresh clean surface. Repeat until the floor is completely free of dirt.

4. Allow the floor surface to dry before walking on it.



SPOT CLEANING WITH TOWELS:

1. Wipe up liquid spills and sweep up dry soil spills as soon as possible.
2. Mix **FastBreak™** Clean and Tack at a dilution ratio of at a ratio of 4 parts water to 1 part Fast Break in a mop bucket / wringer. Use cool water only.
3. Apply **FastBreak™** Clean and Tack solution to towel and wring out thoroughly. Do not apply cleaning solution directly on the wood floor surface.
4. Using the dampened towel, clean the area as required. Use a clean dry towel to wipe up excess cleaning liquid. Avoid leaving excess liquid on wood floor surface.
5. Allow floor surface to dry before walking on it.

SPECIFICATIONS

pH (conc).....	8.9 ± 0.5
pH (1:4).....	7.8 ± 0.3
Specific Gravity (g/cc).....	1.00 ± 0.01
Color.....	Green
Odor.....	Light Citrus
VOC's (%) (at 1:4 dilution).....	<4
Flash Point (°F).....	>201
Flash Point (°F) (at 1:4 dilution).....	None
Freeze-Thaw Stability.....	Excellent
Shelf Life.....	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash hands after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of waste and residues in accordance with local authority requirements.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com