



MATTE™

Satin Gloss Floor Finish

DESCRIPTION

An easy-to-maintain, durable floor coating that produces a satin gloss appearance. Ideal for use in assisted living / nursing centers, especially those that focus on Alzheimer's patients. Perfect for linoleum and other flooring where a high gloss appearance is not desired. Resistant to scuffing, scratching and black heel marks.

PRODUCT FEATURES / BENEFITS

- Low gloss appearance / Recommended for assisted living / nursing centers, especially those that focus on Alzheimer's patients..
- Extremely durable finish / Reduces maintenance and wears exceptionally well.
- Self sealing / does not require the use of a separate sealer.
- Designed for ease of application / May be applied by any personnel without extensive training

DIRECTIONS FOR USE

Floor Preparation: Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply thin uniform coats of MATTE™ Satin Gloss Floor Finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

Routine Maintenance: Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

Interim Maintenance: MATTE™ Satin Gloss Floor Finish is not recommended for burnishing. Scrubbing and Recoating is recommended. Dilute QWIK-SCRUB™ Scrub and Recoat Cleaner in mop bucket according to label dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes. Fill autoscrubber with clear water, mount scrubbing pad or medium grade brush. With vacuum off and squeegee up, scrub the floor until all embedded soils and scuffs are removed from finish. Lower squeegee and vacuum to remove all scrubbing solution. Using clear water from the autoscrubber, rinse floor to remove any excess residue. Allow floor to completely dry prior to re-coating.

SPECIFICATIONS

Type	Metal Bonded Integrated Polymer	Nonslip	Yes
Coverage (sq. ft./gal)	2500 - 3000	Freeze thaw stable	Yes
Drying Time (minutes)	30	Detergent Resistant	Yes
Odor.....	Pleasant	Durability	Superior
Color	White, opaque liquid	Soil Resistance	Superior
pH	8.2 ± 0.2	Scuff Resistance	Superior
Powdering	Nil	Black Mark Resistance	Superior
Film Appearance.....	Clear	Leveling.....	Excellent
Non-yellowing	Yes	Recoatibility	Excellent
Flash Point.....	None	Removability	Excellent
		Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

Meets or exceeds 0.5 coefficient of friction as measured by James Machine Methodology ASTM Method D 2047.

For Commercial and Industrial Use Only



FLOOR CARE



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com