



PIVOT™

Intensive Wood Prep Cleaner

DESCRIPTION

Cleans, conditions existing finish, improving adhesion of new coat of finish. Deep cleans surface to help remove scratches and scuffs from floor.

PRODUCT FEATURES / BENEFITS

- Deep cleaning action removes scratches and scuffs
- Prepares surface for re-coating or burnishing
- Reduces labor time associated with wood floor maintenance
- Cleans & conditions in one-step

DIRECTIONS FOR USE

Wet Screening / Deep Cleaning prior to Recoating:

Wet screening and deep cleaning can only be done on floors that are properly sealed and coated with a water-based wood floor finish.

ROTARY SCREEN / AUTOMATIC SCRUBBER METHOD

1. In a mop bucket / wringer, mix PIVOT™ Intensive Wood Prep Cleaner at 32 ounces concentrate per gallon of cool water (1:4 dilution ratio).
2. Using a clean wet mop, apply PIVOT™ cleaning solution onto the sealed and finished wood floor surface. Do not flood the surface, only get it wet enough to allow the screening to occur without creating dust or drying before it can be vacuumed up.
3. Using a 175 rpm rotary buffer and a choice of Maroon Pad, Brown Pads, Black Stripping pads, or 120-150 grit sanding screen, abrade the surface quickly and thoroughly. Going with the grain of the wood, use overlapping paths to ensure a complete and uniform screening process.
4. Immediately pick up the solution along with the screened material using a wet-vacuum or automatic scrubber.
5. Rinse the floor thoroughly and allow the floor to dry. Use dry towels to remove any standing water or puddles.
6. Tack the floor surface using FAST BREAK™ Routine Wood Cleaner following the Routine Cleaning / Tacking instructions on the FAST BREAK™ product label.
7. Allow the floor surface to dry before walking on it.
8. Recoat with ENDURA™ Ultra Premium Water-Based Urethane Wood Finish.

SPECIFICATIONS

pH.....	6.5 ± 0.5
Color.....	Light Green Liquid
Odor.....	Bland
VOC's (%).....	8.0
VOC's (%) (at 1:4 dilution).....	1.6
VOC's (%) (at 1:16 dilution).....	0.5
Specific Gravity (g/cc).....	1.03 ± 0.01
Flash Point (°F).....	148
Flash Point (°F) (at 1:4 dilution).....	None to Boiling
Flash Point (°F) (at 1:16 dilution).....	None to Boiling
Shelf Life.....	1 year minimum in original unopened container

SAFETY INFORMATION

WARNING: COMBUSTIBLE LIQUID. CAUSES SERIOUS EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN..



Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.


One or more components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail: info@nclonline.com