



WORLD CLASS

Ultra High Speed Sealer / Finish

DESCRIPTION

Utilizing Integrated Fusion Polymer (IFP) technology, this revolutionary floor coating offers the perfect balance of deep wet look gloss with extended gloss retention and exceptional film wearability. IFP technology provides a "tightness" or density to the polymer system that is significantly greater than conventional high speed floor finishes. Because of the enhanced gloss retention of this ultra high speed product, daily burnishing is not required to maintain the maximum gloss. One or two burnishings per week in heavy traffic areas is all that is required to maintain a deep, brilliant gloss. This product is the ideal choice for any ultra high speed maintenance program.

PRODUCT FEATURES / BENEFITS

- Sealer / Finish / Simplifies floor care system
- Immediate deep wet look gloss / Dazzling gloss without burnishing
- Long term gloss retention / Less maintenance needed to keep original lustre
- Utilizes IFP technology / Enhances durability & maximizes resistance to soiling, black heel marks and scuffing
- Enhanced leveling / Easy to use by any service personnel

DIRECTIONS FOR USE

Integrated fusion polymer technology has led to the creation of a very tough, long lasting sealer/finish with a flexible film offering outstanding buffability by high speed buffing or ultra high speed burnishing. Gives outstanding performance on all types of resilient flooring including vinyl, VAT, and vinyl composition tile, also for terrazzo, asphalt, stone and quarry tile and other hard surface floors.

This revolutionary sealer/finish exhibits:

- instant deep wet look
- long term gloss retention
- black mark resistant
- excellent dirt release
- extended restoration cycles
- outstanding leveling
- superior durability
- easy repairability
- user friendly formula

Floor Preparation: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform

coat of sealer/finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to high speed buffing or burnishing the floor surface should be dust or dry mopped. After the floor finish has set for two days damp mopping prior to buffing is also acceptable. When buffing or dry burnishing use a peach or tan buffing pad. Approved mop on restorers or laminators can be used when surface is worn.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

SPECIFICATIONS

| | |
|-------------------------------|---------------------------|
| Type | Integrated Fusion Polymer |
| Color | White, opaque liquid |
| Odor | Typical acrylic |
| pH | 8.2 ± 0.3 |
| Drying Time (minutes) | 30 |
| Specific Gravity (g/cc) | 1.03 ± 0.01 |
| Density (lbs/gal) | 8.6 ± 0.1 |
| Slip Resistant | Yes |

| | |
|--------------------------------|---|
| Freeze Thaw Stable | Yes (3 cycles) |
| Detergent Resistant | Yes |
| Leveling | Excellent |
| Black Mark Resistant..... | Excellent |
| Scuff Resistant | Excellent |
| Resistant to Soiling | Excellent |
| Gloss Retention | Excellent |
| Immediate Wet Look Gloss | Outstanding |
| Shelf Life..... | 1 year minimum in original unopened container |

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



CLASSIFIED Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com



TDS-0570-0814