

For the maximum in durable, long lasting gloss with a minimum of maintenance...

ONE COAT 25

Super High Gloss Floor Finish



This versatile, multi-speed maintenance product produces an ultra-hard wear layer that holds-up even in heavy traffic conditions.



ONE COAT 25 is the perfect choice for areas where infrequent buffing or burnishing is desired. This superior formulation can be maintained with any speed equipment from 175 rpm to 3000 rpm.

FLOOR CARE

ONE COAT 25 Product Benefits:

- For use on any resilient floor surface
- Outstanding resistance to scuffs, scratching and black heel marks
- Can be maintained with conventional, high speed or UHS equipment
- Saves labor and product cost
- Exceptional immediate gloss

Specifications:

Type	Metal Bonded Integrated Polymer	Freeze thaw stable	Yes
Coverage (sq. ft./gal).....	2500 - 3000	Detergent Resistant	Yes
Drying Time (minutes)	30	One Coat Gloss	Superior
Odor.....	Pleasant	Durability	Superior
Color	White, opaque liquid	Soil Resistance	Superior
pH	8.2 ± 0.2	Scuff Resistance	Superior
Powdering	Nil	Black Mark Resistance.....	Superior
Film Appearance.....	Clear	Leveling	Excellent
Non-yellowing	Yes	Recoatibility	Excellent
Flash Point.....	None	Removability	Excellent
Nonslip	Yes	Shelf Life 1 year minimum in original unopened container	

ONE COAT 25

Super High Gloss Floor Finish

Directions for Use:

Floor Preparation: Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coats of ONE COAT 25™ Hi-Gloss Floor Finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing: ONE COAT 25™ Hi-Gloss Floor Finish is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an approved buffing pad. For spray buffing, mop-on or autoscrubber restoring use a preferred NCL gloss restorer.

Routine Maintenance: Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.



Floor Coating and Finishing Material
As to Slip Resistance Only
18EL

Recommended Maintenance Program for One Coat 25

Procedure	Daily	Weekly	Quarterly	Yearly	Bi-Yearly
Dust mopping	4				
Wet Mop or Autoscrub	4	4			
Polish	4	4			
Scrub/Recoat			4	4	
Strip/Recoat					4

Associated Products:

SUPER PURGE

Floor Finish Solubilizer

Unique non-ammoniated formula stripper that quickly liquifies any water based finish. Can be used on even heavily burnished surfaces.



RENU

Ready-to-Use Spray Buff Emulsion

For use with all equipment speeds, this combination of synthetic waxes, polymers and solvents “snaps” back the gloss of floor finishes. Pre-blended for maximum convenience.



IMAGE

Deodorizing Neutral Cleaner

This balanced detergent system is ideal for modern floor maintenance programs. Exceptional Puri™ fragrance enables this product to deodorize as it cleans.

CONTROL

Aerosol Dust Mop Treatment

This balanced detergent system is ideal for modern floor maintenance programs. Exceptional Puri™ fragrance enables this product to deodorize as it cleans.



World Class Cleaning & Hygiene Solutions®

Philadelphia, PA 19123 USA • (800) NAT-CHEM • (215) 922-1200
info@nclonline.com • www.nclonline.com

Distributed by: